

FG Front Blades

FG Front Blades made by Veekmas Ltd have been equipped with parabola lifting arms and a quick coupling. There is a safety box for blade edges at the top. We offer three different kinds of front blade alternatives. The extra hydraulics on the front has floating for blade lifting and leaning.

FG Front Blade – up/down, turning and with a leaning system

- Turns 31° to the right and 23° to the left
- Leaning 12°
- BM quick coupling with mechanical lock
- Height 1,003/956 mm
- Length 1,712/1,675 mm
- Work width 9/10 ft
- Weight 1,720/1,750 kg

FG Multipurpose Front Blade – up/down, turning and with a leaning system

- Hydraulic functions for other accessories, for example ploughs, are possible
- Support arms facilitate assembling of accessories
- Turns 40° to the right and 40° to the left
- Leaning 11°
- BM quick coupling with mechanical lock
- Height 950 mm
- Length 1,700 mm
- Work width 9/10 ft
- Weight 1,910/1,970 kg

FG Front Blade – up/down and turning

- Turns 31° to the right and 23° to the left
- Fixed fastening with bolts
- Height 1,003/956 mm
- Length 1,380/1,343 mm
- Work width 9/10 j
- Weight 1,260/1 280 kg



Front blade – up/down, turning and with a leaning system, a safety box for blade edges and a support arm