

## RG Front Blades

Veekmas Oy manufactures RG front blades which have been equipped with BM quick coupling. The other front blade has FG multipurpose lifting apparatus. The extra hydraulics on the front has floating for blade lifting and leaning.



### Front Blade, high lift – up/down, turning and with leaning

- Turns 40° to the right and to the left
- Leaning 10°
- BM quick coupling, mechanical lock
- Height 850 mm or 1,100 mm
- Length 2,040 mm
- Work width 9 ft or 10 ft
- Clearance from tire to edge 1,925 mm
- Weight 1,460 kg (9 ft, low)
- Weight 1,470 kg (9 ft, high)
- Weight 1,510 kg (10 ft, low)
- Weight 1,520 kg (10 ft, high)

### Front Blade with FG multipurpose lifting apparatus – up/down, turning and with leaning

- Turns 40° to the right and to the left
- Leaning 11°
- BM quick coupling, mechanical lock
- Height 850 mm or 1,100 mm
- Length 1,810 mm
- Work width 9 ft or 10 ft
- Clearance from tire to edge 1,550 mm
- Weight 1,710 kg (9 ft, low)
- Weight 1,750 kg (9 ft, high)
- Weight 1,755 kg (10 ft, low)
- Weight 1,785 kg (10 ft, high)

