

RG Front Blades

RG front blades made by Veekmas Ltd have two alternative lifting apparatus, one with high lift RG lifting apparatus and the other one with FG multipurpose lifting apparatus. Both alternatives have been equipped with BM quick coupling. The extra hydraulics on the front has floating for blade lifting and leaning.



Front Blade, high lift RG lifting apparatus – up/down, turning and with leaning

- Turns 40° to the right and to the left
- Leaning 10°
- BM quick coupling, with mechanical lock
- Height 850 mm or 1,100 mm (10 ft.)
- Length 2,070 mm
- Working width 9 ft. or 10 ft.
- Distance from tire to edge 1,925 mm
- Weight 1,460 kg (9 ft., low)
- Weight 1,510 kg (10 ft., low)
- Weight 1,520 kg (10 ft., high)

Front Blade with FG multipurpose lifting apparatus – up/down, turning and with leaning

- Turns 40° to the right and to the left
- Leaning 11°
- BM quick coupling, with mechanical lock
- Height 850 mm or 1,100 mm
- Length 1,700 mm
- Working width 9 ft or 10 ft
- Distance from tire to edge 1,550 mm
- Weight 1,710 kg (9 ft., low)
- Weight 1,755 kg (10 ft., low)
- Weight 1,785 kg (10 ft, high)

