

RG Front Blades

RG front blades made by Veekmas Ltd have two alternative lifting apparatus, one with high lift RG lifting apparatus and the other one with FG multipurpose lifting apparatus. Both alternatives have been equipped with BM quick coupling. The extra hydraulics on the front has floating for blade lifting and leaning.



Front Blade, high lift RG lifting apparatus – up/down, turning and with leaning

- Turns 40° to the right and to the left
- Leaning 10°
- BM quick coupling, with mechanical lock
- Height 850 mm or 1,050 mm
- Length 2,050 mm or 1,970 mm
- Working width 9 ft or 10 ft
- Distance from tire to edge 1,545 mm or 1,645 mm
- Weight 1,460 kg (9 ft, low)
- Weight 1,470 kg (9 ft, high)
- Weight 1,520 kg (10 ft, low)
- Weight 1,450 kg (10 ft, high)

Front Blade with FG multipurpose lifting apparatus – up/down, turning and with leaning

- Turns 40° to the right and to the left
- Leaning 11° to the right and 13° to the left
- BM quick coupling, with mechanical lock
- Height 850 mm or 1,050 mm
- Length 1,830 mm or 1,750 mm
- Working width 9 ft or 10 ft
- Distance from tire to edge 1,340 mm or 1,390 mm
- Weight 1,710 kg (9 ft, low)
- Weight 1,720 kg (9 ft, high)
- Weight 1,760 kg (10 ft, low)
- Weight 1,700 kg (10 ft, high)

