Veekmas Front Blades

FG Front Blades made by Veekmas Ltd have been equipped with parabola lifting arms and a quick coupling. There is a safety box for blade edges at the top. We offer two different kinds of front blade alternatives. The extra hydraulics on the front has floating for blade lifting and leaning.


FG Multipurpose Front Blade – up/down, turning and with a leaning system

- Hydraulic functions for other accessories, for example ploughs, are possible
- Support arms facilitate assembling of accessories
- Turns 40° to the right and to the left, leaning 11° to the right and 13° to the left
- BM quick coupling with mechanical lock
- Height 1,050 mm
- Length 1,700 mm
- Work width 9 ft /10 ft
- Weight 1,664 kg / 1,702 kg

FG Multipurpose Front Blade – up/down, turning and with a leaning system and tilting system

- Hydraulic functions for other accessories, for example ploughs, are possible
- Support arms facilitate assembling of accessories
- Turns 40° to the right and to the left, leaning 11° to the right and 13° to the left, tilting system 13°
- BM quick coupling with mechanical lock
- Height 1,050 mm
- Length 1,700 mm
- Work width 9 ft /10 ft
- Weight 1,707 kg / 1,745 kg





Front blade – up/down, turning and with a leaning system, a safety box for blade edges and a support arm